

Technical Reference

AWID's Readers and Credentials -- Matching the Technologies

The people who plan access control systems, and who install them, may find it helpful to have a list of the AWID RFID products that work together. Matching the products in the groups below assures compatibility for the credentials and the readers in the installed system.

All of the AWID readers (except SR-2400) have industry-standard Wiegand and RS-232 serial data interfaces. A system can include readers and credentials from different sources, as long as the readers and credentials match each other, and if the code formats are compatible.

Low-Frequency (125 kHz) Products

Proximity R	<u>eaders</u>		Cards, Tags and Wafers – Comp	atible with I	F Readers
SR-2400	MR-1824		CS-AWID Clamshell card	KT-AWID	Keytag (LF)
MM-6800	MR-1824MC	ĺ	GR-AWID Graphics card	PW-AWID	Proximity Wafer
SP-6820	MR-1824HiLo	ĺ	GRMAG-AWID Magnetic-Stripe card		
KP-6840	MR-1824HiLoMC		-		

Ultra-High Frequency (902-928 MHz and 865-868 MHz) Products

Long-Range Readers			Tags and Cards – Compatible with UHF Readers					
LR-2000 LR-2200 LR-3000	LR-2000HiLo LR-test/demo kits		WS-UHF Windshield tag RV-UHF Rearview Mirror tag SV-UHF Sideview Mirror tag VT-UHF Sunvisor tag PT-UHF Portable tag HT-UHF Hangtag	MT-UHF Metal-Mount tag ST-UHF Supertag KT-UHF Keytag CS-UHF Clamshell card GR-UHF Graphics card				
uAxcess Readers								
XR-3600	XK-3640		CS-UHF Clamshell card	KT-UHF Keytag				
XP-3620	UA-612		GR-UHF Graphics card	HT-UHF Hangtag				
<u>Legacy Reader</u>								
LR-911	LR-911HiLo		WS-1216 Windshield tag MT-1014 Metal-Mount tag					